



SPECIFICATION		
Model NO.	LIRDNTHTC5005XESL	LIRDNTTHC5005XESL
Video Output Mode	AHD: 8M@15fps, 5M@20fps/12.5fps, 4MP@30fps/25fps/15fps; 2M@30fps/25fps; CVI: 8M@15fps/12.5fps, 4M/2M@30fps/25fps; TVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps	
Camera		
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor	
Image Resolution	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080	
TV System	PAL/NTSC	
Electronic Shutter	AUTO / MANUAL	
Scanning System	Progressive Scan	
Lens		
Focus Length	2.7-13.5mm	
Focus Control	Auto	
Lens Type	Motorized	
Night Vision		
IR Cut Filter	YES	
Infrared LED	14μ x 24PCS	
Infrared Distance	30M	
IR Power On / Off	AGC Auto Control	
Camera Features		
Starlight	YES	
Day/Night	YES	
OSD Menu	YES	
WDR	YES	
UTC	YES	
Noise Reduction	3DNR	
White Balance	AUTO / MANUAL	
Gain Control	AUTO	
General		
Housing	Metal, IP67	
Bracket	NO	
Operation Temperature	-10℃ ~ +60℃ RH95% Max	
Storage Temperature	-20℃ ~ +60℃ RH95% Max	
Power Source	DC12V±10%, 750mA	
Dimension	Φ 120 x 98(H) mm	
Weight	800g	